



ALLIANCE  
CONSTRUCTION &  
INDUSTRIAL

TRA: **R-3**  
Speed Rating: **A8**

The Alliance 329 is a diamond tread design tire built with a strong nylon construction. Its wide and extended tread protects shoulders and sidewalls against cutting and side snagging. The special cut and chip resistant compound ,heat resistant compound and the tires strong nylon construction provide long life to the tire.

TRACTOR - 23.1-26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Field operation			Not high and sustained torque; Road transport					
								High Tor	Low Torque							
		SW inch	OD inch					6 mph	6 mph	12 mph	Static mph	6 mph	16 mph	19 mph	25 mph	31 mph
23.1-26	DW20	23.1	62.2	27.4	181.1	8PR	13	6090	7960	6830	13070	8530	6310	6090	5690	5180
						145A8	15	6460	8470	7250	13890	9060	6700	6460	6040	5490
							16	6830	8950	7670	14710	9590	7100	6830	6390	5820
						10PR	17	7010	9170	7850	15060	9830	7280	7010	6550	5950
						149A8	19	7340	9590	8220	15760	10300	7610	7340	6860	6240
							20	7670	10030	8600	16490	10760	7960	7670	7170	6530
						12PR	22	8000	10470	8970	17200	11220	8290	8000	7470	6790
						153A8	25	8620	11270	9660	18520	12080	8930	8620	8050	7320
						16PR	28	9220	12060	10340	19820	12940	9570	9220	8620	7850
						159A8	30	9790	12810	10980	21050	13740	10160	9790	9150	8330
							33	10320	13510	11570	22180	14460	10710	10320	9650	8770

Note: For above mentioned size 8 PR is no longer active for production. Recommended rim in red (Bold)

